บริษัท กุลธรเคอร์บี้ จำกัด (มหาชน)
KULTHORN KIRBY PUBLIC COMPANY LIMITED

BRISTOL COMPRESSORS™

System :	English	**Refrigerant :**	R22	**Series Family :**	A
Compressor Model :	H29A683DBV	**Revision :**	0	**BOM ID :**	-

Techninal Specifications

Voltage	Phase	Frequency
415-380	3	50

Application	H	Evaporator temperature Range	-20 °F to 55 °F

Nominal Performance Data @50Hz

Performance	ARI	ASRET	13 SEER B	ARI (45/100)	HEATPUMP
	460	460	460	460	460
Capacity (Btu/hr.)	75900	68200	96200	86700	56700
Motor Input (Watt)	5530	5310	4280	4150	4150
Current (Amp)	9.47	9.08	7.43	7.27	7.22
EER (Btu/W-hr.)	11.9	11.1	19.1	17.8	11.7
Efficiency (%)					
Evaporating Temp.°F	50	45	50	45	30
Condensing Temp.°F	130	130	100	100	110
Ambient Temp.°F	95	95	95	95	95
Liquid Temp.°F	115	115	85	85	95
Return Gas Temp.°F	65	95	65	65	50

Nominal Performance Data @50Hz (±5) based upon 72hr run-in

Mechanical Data

Bore X Stroke (in)	2 x 1.09	Speed (rpm)	2900
Displacement (in^3/rev)	-	IPRV Setting ΔP(psi)	400/500
Displacement (ft^3/hr.)	-	Refrigerant Charge Limit (lbs)	10

Electrical Data

RLA :	9.10	UL Approval :	SA5470	Motor Res. In Ohms (Ω)±5%		
LRA :	82.00	CE Approval :	Yes	T1-T3 (C-R)	T1-T3 (C-S)	T2-T3 (S-R)
MCC :	15.5	CCC Approval	No	2.147	2.147	2.147
Voltage Range :	342/457					
Protection Type :	Internal Line Break					

Electrical Accessories Components

Start Relay : ()

Start Cap (µFd/volts) :

Run Cap (µFd/volts) : (Parenthesis Denote Med. Torque Components)

PTCR Start Device : Ceramite P/N : PTCR Start Device : AC Ohms :

Crankcase Heater Vendor P/N : Sensata 9HT5

Type-watts : PCTR - 47

Misc. Technical Info

Oil Name :	3GS Mineral Oil	Polyolester 32BCE		
Oil Spec :	581003	CE Approval :	Recharge :	
Viscosity : (cSt @40°C)	29.5	65	62	
			Weight Net	
Sound Power (dBA) :	Internal Free Volume (in^3)	Max. Compressor Height (in)	Net (lbs)	Ship (lbs)
	680	17.375	97	101

Certificate Marks

REV. DATE 22-10-2020 **C/N No. 0004/20**